

Building A Sustainable Future

GRIZZL^E™

Smart EV Charger



Grizzl-E Smart EVSE is the revolutionary Smart EV Charger. The first mass-produced, affordable EV Charger in North America that can connect to any OCPP 1.6J software.

With OCPP, Grizzl-E Smart is the most versatile EV Charging solution on the market. Grizzl-E Smart becomes your tool to do what you need your EVSE to do. With third-party software providers, Grizzl-E Smart can power share, provide authentication, collect payments, set a charging schedule, track usage, participate in Demand/Response Utility programs, and work in multifamily and fleet environments.

Don't pay more and get stuck with only the manufacturer's software. Go with Grizzl-E Smart and discover limitless possibilities.

- ⚡ Wi-Fi Connected
- ⚡ Compatible with any OCPP 1.6 Application
- ⚡ Energy Star Certified
- ⚡ Up to 30 miles per hour charging speed
- ⚡ IP67 Water- and Fire-resistant Indoor Enclosure
- ⚡ Heavy-Duty, compact, rigid, and robust design
- ⚡ Made in Canada





Water- and Fire-resistant
cast aluminum enclosure.
Indoor/Outdoor Rated -30C -
50C (-22°F to 122°F).



Easy to install with included
mounting bracket and
security pin. Easy to use and
move.



UL Tested and Certified.
3-year or 5-year replacement
warranty.

90 Gough Road, Unit 2
Markham, Ontario L3R 5V5 Canada
+1-833-840-4970
info@unitedchargers.com
www.grizzl-e.com



Product Features:

Model Number: GRS-14-24-P, GRS-6-24-P

J1772 AC Level 2 (208-240 VAC), 40A Continuous Rated (10.0 kW)

- **Enclosure**

NEMA 4X Indoor/Outdoor Rated Aluminum Cast Enclosure

- **Dimensions**

EVSE: 10.25 x 6.25 x 3.75 inches (26.0 x 16.0 x 9.3 cm)

- **Operational Ratings**

Temperature: -22°F - 122°F (-30°C - 50°C); Humidity: 95% RH non-condensing

- **Adjustable Maximum Output Ratings**

40A; 10.0 kW Maximum Output – For use with 50A Circuit Rating;
32A; 7.68 kW Maximum Output – For use with 40A Circuit Rating;
24A; 5.76 kW Maximum Output – For use with 30A Circuit Rating;
16A; 3.84 kW Maximum Output – For use with 20A Circuit Rating.

- **Charge Cable Length**

24 ft. (7.2m)

- **Wi-Fi Connection**

Connects to 2.4Ghz Wi-Fi network,

- **OCPP Compatibility**

Compatible with all OCPPj 1.6 commands.

- **Cable & Connector Management**

EasyEvPlug™ Holster and cable management system for J1772 or Tesla.

- **Portable and Hardwire ready**

NEMA 14-50 or NEMA 6-50 Electrical Plug. Hardwired by licensed electrician.

- **Simple, Flexible Mounting Options**

Wall Mount with security features (including single stud mount), Pedestal,
Bollard/Pole (Single & Dual Port) available from United Chargers.

- **Electrical Circuit / Input Power Requirements**

Circuit Requirement: Dedicated Single Phase 208-240VAC, 50/60 Hz;
Branch Breaker: Double pole; Circuit Conductors: Line 1, Line 2, Ground.

- **Display & Indicators**

LED Charge Status Indicators (Ready, Charging, Fault, Connected).

- **Safety Features**

Over Current, Over Voltage, Under Voltage, Missing Diode, Ground Fault, and
Over Temperature Protections. Self-Monitoring and Recovery, Power Outage
Recovery. Built in GFCI.

- **UL Certified for USA and Canada**

